

MATERIAL SAFETY DATA SHEET

B70W211
13 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER	B70W211	HMIS CODES	
		Health	2
		Flammability	0
		Reactivity	0
PRODUCT NAME	Water Based Catalyzed Epoxy (Part A), Extra White		
MANUFACTURER'S NAME	THE SHERWIN-WILLIAMS COMPANY	EMERGENCY TELEPHONE NO.	(216) 566-2917
	101 Prospect Avenue N.W. Cleveland, OH 44115		
DATE OF PREPARATION	11-MAY-06	INFORMATION TELEPHONE NO.	(216) 566-2902

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
2	112-34-5	2-(2-Butoxyethoxy)-ethanol		
		ACGIH TLV	Not Available	0.06 mm
		OSHA PEL	Not Available	
2	107-21-1	Ethylene Glycol		
		ACGIH TLV	100 mg/m3 CEILI (aerosol)	0.12 mm
		OSHA PEL	50 ppm CEILING	
15	13463-67-7	Titanium Dioxide		
		ACGIH TLV	10 mg/m3 as Dust	
		OSHA PEL	10 mg/m3 Total Dust	
		OSHA PEL	5 mg/m3 Respirable Fraction	

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE
 INHALATION of vapor or spray mist.
 EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE
 EYES: Irritation.
 SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.
 In a confined area vapors in high concentration may cause headache, nausea or dizziness.

SIGNS AND SYMPTOMS OF OVEREXPOSURE
 Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
 None generally recognized.

CANCER INFORMATION
 For complete discussion of toxicology data refer to Section 11.

=====
Section 4 -- FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes.
Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing.
Keep warm and quiet.

INGESTION: Do not induce vomiting.
Get medical attention immediately.

=====
Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT
>200 F PMCC

	LEL	UEL
	N.A.	N.A.

FLAMMABILITY CLASSIFICATION
Not Applicable

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

=====
Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.
Remove with inert absorbent.

=====
Section 7 -- HANDLING AND STORAGE

STORAGE CATEGORY

DOL Storage Class IIIB

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

=====
 Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION
 =====

 PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits.

Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PRECAUTIONS

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

 =====
 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES
 =====

PRODUCT WEIGHT	9.68 lb/gal	1159 g/l
SPECIFIC GRAVITY	1.16	
BOILING POINT	212 - 448 F	100 - 231 C
MELTING POINT	Not Available	
VOLATILE VOLUME	62 %	
EVAPORATION RATE	Slower than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	N.A.	
pH	9.0	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)		
1.04 lb/gal	125 g/l	Less Water and Federally Exempt Solvents
0.44 lb/gal	53 g/l	Emitted VOC

 =====
 Section 10 -- STABILITY AND REACTIVITY
 =====

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

Continued on page 4

=====
 HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide
 HAZARDOUS POLYMERIZATION
 Will not occur

 =====

 Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.
 Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver and urinary systems.

Rats exposed to titanium dioxide dust at 250 mg./m3 developed lung cancer, however, such exposure levels are not attainable in the workplace.

TOXICOLOGY DATA

CAS No.	Ingredient Name				
112-34-5	2-(2-Butoxyethoxy)-ethanol	LC50	RAT	4HR	Not Available
		LD50	RAT		5660 mg/kg
107-21-1	Ethylene Glycol	LC50	RAT	4HR	Not Available
		LD50	RAT		4700 mg/kg
13463-67-7	Titanium Dioxide	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available

Section 12 -- ECOLOGICAL INFORMATION -----

ECOTOXICOLOGICAL INFORMATION

No data available.

 =====

Section 13 -- DISPOSAL CONSIDERATIONS -----

WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container.
 Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

 =====

Section 14 -- TRANSPORT INFORMATION -----

No data available.

=====
Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
107-21-1	Ethylene Glycol	2	
	Glycol Ethers	3	

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

=====
Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.